



COMAC 1



CA Wet&Dry 1 Motor: practical and professional wet and dry vacuum cleaners

The professional wet and dry single motor vacuum cleaners of the CA Wet&Dry range have been designed to provide practicality and professional results.

They are vacuum cleaners equipped with high capacity tanks but designed to be practical and easy to use. Resistant and easy to handle, they are used for the cleaning of medium surfaces or for the collection of solid material of various sizes, as well as liquids.

The versatility and performance of these professional vacuum cleaners make them suitable for cleaning companies, demanding applications and also for rental in the public, in Ho.Re.Ca., wellness & Sports, and public sectors.

KEY FACTORS OF THE CA WET&DRY 1 MOTOR RANGE:

- Available with polyethylene or stainless steel tank.
- Optional front fixed accessory for easy liquids suction on large surfaces, available on demand.
- Possibility to choose versions with fixed trolley.
- Some models can be equipped with an optional quick drain kit to facilitate emptying operations.
- CA80 is equipped with a drain hose, accessory holder and a special opening for rinsing out the interior of the tank.
- Standard cloth filter.
- Standard sponge filter.
- Cartridge filter, washable cartridge filter, HEPA cartridge filter and nylon filter available as optional.
- Wide choice of available accessories that make the range of CA WET&DRY 1 motor vacuum cleaners extremely customizable.



MODELS

CA30

Tank capacity: 30 l
Professional WET & DRY
Suction: 1 motor

CA60

Tank capacity: 60 l
Professional WET & DRY
Suction: 1 motor

CA80

Tank capacity: 80 l
Professional WET & DRY
Suction: 1 motor

CA P25 WD

Tank capacity: 35 l
Professional WET & DRY
Suction: 1 motor

CA A27WD

Tank capacity: 35 l
Professional WET & DRY
Suction: 1 motor

CA P40 WDM

Tank capacity: 60 l
Professional WET & DRY
Suction: 1 motor

Details that matter



Thanks to their ergonomic handle these vacuum cleaners are easily transportable over all floors. Fixed trolley versions are even easier to maneuver.

CA80 can be equipped with a front squeegee, controlled by a pedal placed at the rear of the machine, designed for quick and easy floor drying operations.



CA80 is equipped with a standard drain hose, while for CA P40 WDM a quick drain kit is available as optional.

The convenient net bag of the CA80 incorporated onto the rear of the unit, can hold all the accessories to keep them handy at all times.



The optimal tilt angle between the handle and the rear wheels allows CA80 to rest completely on the ground to favor a better emptying of the tank.



REFERENCE SECTORS



Cleaning companies



Health



Public



Ho.Re.Ca



Well-being and sports



Handicraft



Automotive

Available kits and accessories for the CA Wet&Dry 1 motor range



225438 KIT Basic Ø 37 mm
CA30 CA60
109920 109921

• •



225439 KIT Extra HE Ø 32 mm
CA80 CA P25 WD
109922 109914
CA A27 WD CA P40 WDM
109924 109916

• •



405431 Paper filter bag
CA30 CA60 CA P25 WD
109920 109921 109914
CA A27 WD CA P40 WDM
109924 109916

◊ ◊ ◊



405430 Paper filter bag
CA80
109922

◊



443005 Microfiber filter bag
CA30 CA60 CA P25 WD
109920 109921 109914
CA A27 WD CA P40 WDM
109924 109916

◊ ◊ ◊



443001 Microfiber filter bag
CA80
109922

◊



204652 Cloth filter

•



405436 Cartridge filter

◊



405433 Washable cartridge filter

◊



405434 HEPA cartridge filter

◊



405429 Sponge filter

•



405432 Nylon filter

◊



204571 Front squeegee
CA80
109922

◊



221157 Drain kit
CA80
109922

•

Legend

• standard ◊ optional

| TECHNICAL DESCRIPTION | CA30 | CA60 | CA80 | CA P25 WD | CA A27WD | CA P40 WDM | |
|-----------------------|---|-------------------------------|-------------------------------|-----------------------------|-------------------------------|-------------------------------|-----------------------------|
| Voltage-Frequency | V-fase-Hz | 220/240-1-50/60 * | 220/240-1-50/60 * | 220/240-1-50/60 * | 220/240-1-50/60 * | 220/240-1-50/60 * | |
| Power | W-Hp | 1000 | 1000 | 1000 | 1000 | 1000 | |
| Motor | n./type | 1/Bypass double stage | 1/Bypass double stage | 1/Bypass double stage | 1/Bypass double stage | 1/Bypass double stage | |
| Water lift | mmH ₂ O/inchH ₂ O | 2100/82,6 | 2100/82,6 | 2100/82,6 | 2300/90,5 | 2300/90,5 | |
| Airflow | l/s / gal/s | 52/54,9 | 52/54,9 | 52/54,9 | 54/57 | 54/57 | |
| Tank capacity | l/gal | 30/31,7 | 60/63,4 | 80/84,5 | 35/36,9 | 60/63,4 | |
| Cable length | m/feet | 7/22,9 | 7/22,9 | 7/22,9 | 7/22,9 | 7/22,9 | |
| Noise level | dB | 72 | 72 | 70 | 70 | 70 | |
| Dimensions (Lxhxw) | mm/inch | 425x450x630 16,7x17,7x24,8 | 425x450x760 16,7x17,7x29,9 | 480x605x915 18,8x23,8x36 | 378x400x670 14,8x15,7x23,6 | 470x470x775 18,5x18,5x30,5 | 510x575x930 20x22,6x36,6 |
| Weight | Kg/lbs | 10/22 | 12/26,4 | 15/33 | 8/17,6 | 9/19,8 | 14/30,8 |

*other voltages available on request



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Organisation certified by Q.C.B. Italia ISO 9001:2015, ISO 14001:2015, ISO 45001:2018

